

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

luxaprint® shellac color without yellow, black

UFI: 686Y-K0P4-200X-CNCS; 8T4Y-Y0XC-V00H-3UFP; D80Y-50CA-N009-2RK8;  
FQ4Y-G07Y-K001-FGVM; H4C0-5162-300T-VAXR; T56Y-20YQ-S00F-Q9SQ;  
TC6Y-30CH-D00E-1YXU

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Ligth curing lacquer for use in audiology.

### 1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH  
Street: Carl-Zeiss-Straße 4  
Place: D-76275 Ettlingen  
Telephone: +49 7243/510-0  
Telefax: +49 7243/510-100  
e-mail: post@detax.com  
Internet: www.detax.com  
Responsible Department: This number is only obtainable during office hours  
(Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

### 1.4. Emergency telephone number:

+1-800-424-9300 (CHEMTREC worldwide)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1907/2006

Flam. Liq. 2; H225  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
Skin Sens. 1; H317  
STOT SE 3; H335  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No. 1907/2006

#### Hazard components for labelling

"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"  
acrylic acid derivates  
aliphatic polyestertriurethane triacrylate  
vinylester resin  
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Danger

#### Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 2 of 12

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container in accordance with local and national regulations.

#### Special labelling of certain mixtures

EUH210	Safety data sheet available on request.
--------	---

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of acrylic/ methacrylic resins with auxilliary matters.

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No. 1907/2006)			
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"			40 - < 60 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
	acrylic acid derivates			25 - 50 %
	Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 3; H319 H317 H412			
	aliphatic polyestertriurethane triacrylate			5 - 20 %
	Skin Sens. 1A, Aquatic Chronic 4; H317 H413			
55818-57-0	vinylester resin			0.1 - < 5 %
			01-2119490020-53	
	Skin Sens. 1, Aquatic Chronic 2; H317 H411			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			0.1 - < 5 %
	278-355-8	015-203-00-X	01-2119972295-29	
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361 H317 H411			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 3 of 12

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"	40 - < 60 %
		inhalation: LC50 = 78 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 7870 mg/kg	
		acrylic acid derivates	25 - 50 %
		dermal: LD50 = 2000 mg/kg; oral: LD50 = 2000 mg/kg	
		aliphatic polyestertriurethane triacrylate	5 - 20 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
55818-57-0		vinylester resin	0.1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
75980-60-8	278-355-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	0.1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

###### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

###### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

###### After ingestion

Let water be drunken in little sips (dilution effect).  
Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

##### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

##### 5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

##### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

##### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 4 of 12

#### General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

#### 6.3. Methods and material for containment and cleaning up

##### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidising agent . Pyrophoric or self-heating substances.

#### Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs. Keep away from all kind of lighth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

### 7.3. Specific end use(s)

Lacquer for coating of earmoulds. For use by trained specialist staff.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 5 of 12

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
Worker DNEL, long-term		inhalation	systemic	0,822 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	0,233 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,145 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	0,0833 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,0833 mg/kg bw/day

#### 8.2. Exposure controls

##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

##### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Pale blue
Odour:	faintly like esters

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	92 °C DIN 51356
Flammability	
Solid/liquid:	not applicable
Gas:	not applicable
Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Flash point:	12 °C DIN 51755
Auto-ignition temperature:	>400 °C DIN 51794
Decomposition temperature:	>100 °C
pH-Value:	not determined

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 6 of 12

Water solubility: (at 20 °C)	16 g/L
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	40 hPa
Vapour pressure: (at 50 °C)	160 hPa
Density (at 20 °C):	1,07 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

##### Explosive properties

The product is not: Explosive.

##### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

##### Oxidizing properties

Not oxidizing.

##### Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Reacts with : oxidising agents, radicals forming substances or heavy metal ions.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

Ultra-violet light and daylight initiate polymerisation of the product. Therefore keep only in tightly closed containers away from any sources of light. Keep at temperature between 15°C/ 59°F and 25°C/ 77°F.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

In case of fire, acrid acrylic fumes may occur.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No. 1907/2006

#### Acute toxicity

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"				
	oral	LD50 mg/kg	7870	Rat	
	dermal	LD50 mg/kg	>5000	Rabbit	
	inhalation (4 h) vapour	LC50	78 mg/l	Rat	
	acrylic acid derivates				
	oral	LD50 mg/kg	2000	Rat	OECD 423
	dermal	LD50 mg/kg	2000	Rabbit	OECD 402
	aliphatic polyestertriurethane triacrylate				
	oral	LD50 mg/kg	> 5000	Ratte	Lieferanten-SDB OECD 423
	dermal	LD50 mg/kg	> 2000	Ratte	Lieferanten - SDB OECD 402
55818-57-0	vinylester resin				
	oral	LD50 mg/kg	>2000	Rat	OECD 401
	dermal	LD50 mg/kg	>2000	Rat	OECD 402
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 mg/kg	>5000	Rat	
	dermal	LD50 mg/kg	>2000	Rat	

#### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. ("methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"; acrylic acid derivates; aliphatic polyestertriurethane triacrylate; vinylester resin; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. ("methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA")

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 8 of 12

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
80-62-6	"methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate, MMA"					
	Acute fish toxicity	LC50 >100 mg/l	96 h			
	acrylic acid derivatives					
	Algae toxicity	NOEC 10 mg/l	72 d	Pseudokirchneriella subcapitata		OECD 201
	aliphatic polyesterurethane triacrylate					
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna	Lieferanten -SDB	OECD 202
	Acute bacteria toxicity	(EC50 > 100 mg/l)		Pseudokirchneriella subcapitata	Lieferanten - SDB	OECD 201
55818-57-0	vinylester resin					
	Acute fish toxicity	LC50 >100 mg/l	96 h			OECD 201
	Acute crustacea toxicity	EC50 >100 mg/l	48 h			OECD 202
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute algae toxicity	ErC50 >2,01 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 3,53 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(EC50 >1000 mg/l)	3 h	Activated sludge		

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
55818-57-0	vinylester resin			
		42%	28	
	Not readily biodegradable (according to OECD criteria)			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
		0-10%	28	
	Not readily biodegradable (according to OECD criteria)			

### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
55818-57-0	vinylester resin	3,8
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1

#### BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	47-55	Cyprinus carpio (Common Carp)	



## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 9 of 12

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Not identified as PBT/ vPvB substances

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1866
<u>14.2. UN proper shipping name:</u>	RESIN SOLUTION
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	I
Hazard label:	3
Classification code:	F1
Limited quantity:	500 mL
Excepted quantity:	E3
Transport category:	1
Hazard No:	33
Tunnel restriction code:	D/E

#### Other applicable information (land transport)

Flammable liquid

#### Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1866
<u>14.2. UN proper shipping name:</u>	Resin solution
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	I
Hazard label:	3
Classification code:	F1
Limited quantity:	500 mL
Excepted quantity:	E3

#### Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 1866
<u>14.2. UN proper shipping name:</u>	RESIN SOLUTION
<u>14.3. Transport hazard class(es):</u>	3

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 10 of 12

<b>14.4. Packing group:</b>	I
Hazard label:	3
Special Provisions:	-
Limited quantity:	500 mL
Excepted quantity:	E3
EmS:	F-E, S-E

**Other applicable information (marine transport)**

Flash point: 12°C c.c.

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	RESIN SOLUTION
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	Forbidden
Passenger LQ:	Forbidden
Excepted quantity:	E3
IATA-packing instructions - Passenger:	351
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	361
IATA-max. quantity - Cargo:	30 L

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### luxaprint® shellac color without yellow, black

Revision date: 23.01.2023

Product code: 10571.5

Page 11 of 12

CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%  
 CLP: Classification, labelling and Packaging  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 UN: United Nations  
 DNEL: Derived No Effect Level  
 DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
 intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 SVHC: Substance of Very High Concern

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1907/2006

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006

### **luxaprint® shellac color without yellow, black**

Revision date: 23.01.2023

Product code: 10571.5

Page 12 of 12

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*